

**Designation:** Retractable Fall Arrester in webbing

- Webbing width: 50 mm
- Minimum breaking strength: > 15 kN
- Fall indicator at the top of the device
- Protective casing
- Energy Absorber width 45 mm.

**Connectors:**

1 snap hook, opening 17 mm, ref. FA 50 202 17, et 1 steel scaffold hook, ref. FA 50 207 55.

**Compliance :** Conforms to EN 360:2002



18 cm

**Length:** 2.50 m

**Materials of the components :**

Casing : Polyethylene anti shock  
 Webbing : Polyamide / Polyester  
 Connector : Steel

**HS code**

84289090

**Carton Size / Pieces**

40x80x24 / 20

**Unit Weight**

1,70 kg

**AET : N°2194 Issue 5 Extension 12**

Satra Technology Centre, N°0321  
 Wyndham Way, Telford Way, Kettering,  
 Northamptonshire, NN16 8SD, United Kingdom.

**Article 11: GB07/73551**

SGS United Kingdom Ltd., N° 0120  
 Unit 202B, Worle Parkway,  
 Weston-super-Mare, BS22 6WA, United Kingdom



MAJ : 07/14

**ZI les portes du Dauphiné**

**4 rue de l'Aigüe**

**69 780 St Pierre de Chandieu – France**

**Tel : +33 (0)4 72 48 78 27 Fax : + 33 (0)4 72 48 58 32**

**www.kratossafety.com info@kratossafety.com**

