



GasAlert MicroClipXT

multi-gas detector



Multi-gas made simple

The slim and compact GasAlertMicroClip XT provides affordable protection from atmospheric hazards. With the addition of IntelliFlash™, this multi-gas detector offers continuous visual confirmation of detector operation and compliance. Simple one-button operation offers ultimate ease of use and significantly reduces time spent training the user. The GasAlertMicroClip XT is fully compatible with BW's MicroDock II automatic test and calibration system.



H₂S

CO

O₂

LEL

**WATER
RESISTANT**



BW
Technologies
by Honeywell




Wear yellow. Work safe.

- Continuous visual compliance with IntelliFlash™
- Multi-gas versatility with one-button simplicity
- Incredibly thin and lightweight, making it comfortable to wear
- Extraordinarily low cost of ownership

Standard features of BW products:

- Continuous LCD shows real-time gas concentrations
- Compact and lightweight design makes it comfortable to wear
- Water-resistant
- Simple automatic calibration procedure; compatible with BW MicroDock II automatic test and calibration station
- Full function self-test of sensor, battery status, circuit integrity and audible/visual alarms on start up
- Bright wide-angled visual alarm bars
- Built-in concussion-proof boot
- Conveniently manage your fleet using Fleet Manager II

GasAlertMicroClip XT Specifications

Size	4.4 x 2.4 x 1.1 in. / 11.3 x 6.0 x 2.9 cm	
Weight	6 oz. / 171 g	
Temperature	-4 to +136°F / -20 to +58°C	
Humidity	0% - 95% RH (non-condensing)	
Alarms	- Visual, vibrating, audible (95 dB) - Low, High, STEL, TWA, OL (over limit)	
Tests	Audible/visual alarms on activation, sensors, battery and circuitry (continuous)	
Typical battery life	10 hours (typical); recharges in less than 4 hours	
User options	Confidence beep Set STEL interval Sensor on/off Latching alarms Safe display mode Stealth mode Calibration lock Auto zero on start up O ₂ auto calibration on start up Set bump test interval IntelliFlash interval Combustible gas measurement (% LEL or % by volume methane) User-settable calibration gas level Force bump test when overdue Force calibration when overdue Low alarm acknowledge Language choices (five) Set custom start up message	
Ratings	EMI/RFI: Complies with EMC Directive 2004/108/EC IP 66/67	
Certifications and approvals	 Class I, Div. 1, Gr. A, B, C, D  American Bureau of Shipping ATEX:  II 1 G Ex ia IIC T4 Ga IECEX: Ex ia IIC T4 Ga CE: European Conformity	
Warranty	Full two-year warranty including all sensors	

Additional GasAlertMicroClip XT features:

- IntelliFlash verifies operation and compliance to both the user and supervisor
- Tamper-proof, one button operation
- Equipped with internal vibrating alarm for high noise areas
- Powered by a lithium polymer battery
- Multi-language support in English, French, German, Spanish and Portuguese

Options and Accessories



MicroDock II compatible



Auxiliary filter kit



IR connectivity kit



Five unit cradle charger


For a complete list of accessories, please contact BW Technologies by Honeywell.

Sensor Specifications

Gas	Measuring Range	Resolution
H₂S	0-100 ppm	1 ppm
CO	0-500 ppm	1 ppm
O₂	0-30.0%	0.1%
Combustible gases	0-100% LEL 0-5.0% v/v	1% 0.1%

Alarm setpoints for all sensors are user adjustable. Setpoints are automatically displayed during instrument start up. Lower resolution for H₂S optional.

Locally available from



DUE TO ONGOING RESEARCH AND PRODUCT IMPROVEMENT, SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.



SEDE:

Av. Infante D. Henrique - lote 9B, Lisboa
Tel: 217 577 212 | sintimex@sintimex.pt

MAIA:

Rua Engº Frederico Ulrich nº2025 Moreira, Maia
Tel: 229 419 084 | norte@sintimex.pt

ANGOLA:

Centro de Logística Talatona, Armazém E-05,
Via C3A - Gleba GU03, Talatona
Tel: (+244) 927 366 596 | comercial@hsa-angola.com

MOÇAMBIQUE:

Av. Romão Fernandes Farinha nº 171, Maputo
Tel: (+258) 845 130 039 | comercial@sintimex.co.mz