

Nitrotough™ N230Y & N250Y

DESCRIPTION

- Industrial protective glove.
- Nitrile supported glove.
- 2 versions available : three-quarter dip (N230Y) and fully dipped (N250Y).
- 6 sizes available : 6 (only N230Y), 7, 8, 9, 10 and 11.
- Trade unit 12 pairs, 144 pairs in a transit case.

CHARACTERISTICS

- Interlock 100% cotton liner.
- Knit wrist for snug fit.
- Nitrile coating.

PERFORMANCES

- Very good abrasion resistance.
- Comfort and flexibility optimum.
- Excellent dexterity.
- In compliance with the standards EN 420 (General requirements) and EN 388 (Mechanical hazards) by the notified laboratory INSPEC.

APPLICATIONS

- For all type of work requiring protection against light to moderate mechanical aggression.
- Sector of activity : construction, refuse collection, general handling work.

LIMITATIONS

- Do not use for handling liquids or pointed objects.



This glove is certified to comply with the essential requirements of European Directive EEC/89/686 of December 21st, 1989 relative to personal protective equipment submitted to CE type examination issued by a notified laboratory, who certifies the conformity of this glove with the EN standards to which it responds and certifies the performance levels obtained during tests.



EN 420



4111

EN 388

Mechanical hazards

EN 388

4 Abrasion

1 Cut

1 Tear

1 Puncture

EN 420

5 Dexterity

Order codes

Sizes	6 (XS)	7 (S)	8 (M)	9 (L)	10 (XL)	11 (XXL)
Nitrotough™ N230Y	200QY0586	200QY0587	200QY0588	200QY0589	200QY0580	200QY0581
Nitrotough™ N250Y		200QB0587	200QB0588	200QB0589	200QB0580	200QB0581