

NITROTOUGH™ N650 / N660



DESCRIPTION

- 5-fingered protective glove.
- Nitrile supported glove.
- 2 versions available :
 - knit wrist : N650
 - safety cuff : N660
- 4 sizes available : 8, 9, 10 and 11.

CHARACTERISTICS

- 100% cotton fleeced liner.
- Full nitrile coating.



4221



EN 388 : 1994
Mechanical Hazards

This glove is certified to comply with the essential requirements of European directive EEC/89/686 of December 21st, 1989 relative to personal protective equipment submitted to CE type examination issued by a notified laboratory, who certifies the conformity of this glove with the EN standards to which it responds and certifies the performance levels obtained during tests.

EN 388 : 1994			
Abrasion	Cut	Tear	Puncture
4	2	2	1

PERFORMANCES

- Complete hand protection in wet and/or polluted working environments owing to the full coating.
- Tough and flexible.
- Very good resistance to abrasion.
- Excellent grip.
- Certified in conformity with the standards **EN 420:1994** (General requirements) and **EN 388:1994** (Mechanical hazards) by the notified laboratory INSPEC.

APPLICATIONS

- Ideal for intensive use.
- Examples of applications : heavy mechanical handling, fabrication or site cleaning.

References

	Size 8	Size 9	Size 10	Size 11
N650	200FB0508	200FB0509	200FB0500	200FB0501
N660	200FB0708	200FB0709	200FB0700	200FB0701

