

# BAXTER

## COMFORT AND INGENUITY

BAXTER, the alternative to the TRACKER model, offers total comfort thanks to its highly wrap-around frame. With its waterproof foam and ingenious system for attaching the strap, BAXTER offers effective protection from sprays of solids and liquids, and from dust.

BAXTER will soon be available in the RX range.

 PLATINUM®



BAXPSI



BAXPSF



BAXCSP



49 g



Foam and strap



Attachment system

- + INCREASED PROTECTION**
- + WRAP-AROUND FRAME**
- + WATERPROOF FOAM AND REMOVABLE STRAP**
- + COATING  PLATINUM® (+P)**

**bolle**  
SAFETY

# BAXTER

## COMFORT AND INGENUITY

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
<b>BAXTER</b>	Clear	BAXPSI	2C-1,2  1 BT KN €€	EN166 FT €€	Anti-scratch /Anti-fog ()
	Smoke	BAXPSF	5-3,1  1 BT KN €€	EN166 FT €€	Anti-scratch /Anti-fog ()
	<b>bCSP</b>	BAXCSP	5-1,4  1 BT KN €€	EN166 FT €€	Anti-scratch /Anti-fog ()
<b>Strap version</b>	With strap & foam	-	-	EN166 3 4 5 BT €€	Anti-scratch /Anti-fog ()

### LENS MARKING

#### Optical class symbols:

1. Continuous work

#### Mechanical strength symbols:

**F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

**T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

**B.** Impact à moyenne énergie, résiste à une bille de 6 mm et de 0,86 g à 120 m/s.

#### Others symbols:

**K.** Resistance to surface damage by fine particles (optional)

**N.** Resistance to fogging (optional)

€€ European standard Manufacturer name

### FRAME MARKING

**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

**3.** Liquid droplets.

**4.** Large dust particles > 5 microns.

**5.** Gas and fine dust particles < 5 microns.

**F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

**T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

**B.** Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s.

€€ European standard Manufacturer name

**Bollé Safety product approval certificates to CE standards will be sent on request.**

### TECHNOLOGY

#### **bCSP**

This innovating coating is an effective solution for all activities that alternate exposure to bright light and low light, while also being suitable for extreme hot and cold temperature environments.

CSP is also combined with the exclusive PLATINUM coating that sustainably combats fogging.

#### **PLATINUM**

The new exclusive scratch and fog resistant coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and durably delays the appearance of fogging.

### CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.

### PACKAGING AND EAN13 CODE

	BAXPSI	BAXPSF	BAXCSP
Individual plastic bag	3660740007744	3660740007751	3660740007768
10 safety spectacles per inner box	3660740107741	3660740107758	3660740107765
240 safety spectacles per outer pack	3660740207748	3660740207755	3660740207762

### CHARACTERISTICS

LENSES	PC - 2,2 mm - Curve 8
FRAME	PC
TEMPLES	PC
STRAP	Nylon
FOAM	PC + EVA



03/08/2016

Europe Bollé Safety  
95 rue Louis Guérin  
69100 Villeurbanne - France  
Tél. : 00 33 (0) 4 78 85 23 64  
Fax : 00 33 (0) 4 78 85 28 56  
contact@bolle-safety.com

**bolle-safety.com**

U.K. Bollé Safety  
Unit C83 - Barwell Business Park Leatherhead Road - Chessington  
Surrey - KT9 2NY  
Tél. : 00 44 (0)208 391 4700  
Fax : 00 44 (0)208 391 4733  
e-mail : sales@bolle-safety.co.uk

**bolle**  
SAFETY